

# MultiBio 800

## Multi-biometric Access Control and Time Attendance Terminal



MultiBio 800 is a time attendance and access control terminal for face and fingerprint verification. Using ZK latest ZKFACE 7.0 high-speed face recognition algorithm, it has extremely high verification speed and low error rate, and is able to effectively prevent duplicated registration.

With its high-resolution infrared night vision light and professional color duo camera, the terminal can carry out quick verification in any environment. What is more, it supports face, fingerprint, user ID, password, RFID card and various combination methods, in order to satisfy the demands of different users. Moreover, the TCP/IP communication supports connection across internet segments. Its auxiliary input function can be used for linking to Fire Alarm.

### Features

- 2.8-inch color display with graphical UI for easy operation
- Effectively prevent duplicated face registration
- Multiple Verification Modes: Multi-verification methods (card is optional) providing user various choices
- Full Access Control Features: Anti-passback, access control interface for 3rd party electric lock, door sensor, exit button, alarm and doorbell
- Good Performance in Dark Environment, Infrared optical system enables machine to work well at night
- Built-in auxiliary input with enhanced flexibility to link with wired detector or emergency switch

# Specifications

|                          |  |
|--------------------------|--|
| Display                  | 2.8 inch TFT LCD Color Screen  |
| Face Capacity            | 800 Face   |
| Fingerprint Capacity     | 1,000 Templates  |
| Card Capacity            | 5,000 EM or Optional Mifare card   |
| Transaction Capacity     | 100,000 Transactions   |
| Algorithm Version        | ZKFinger VX10.0 & ZKFace VX7.0   |
| Communication            | RS485, TCP/IP, USB-host  |
| Access Control Interface | 3rd Party Electric Lock, Door Sensor, Exit Button, Alarm, Doorbell, Wiegand In/Out |
| Aux. Input               | 1ea for linkage function   |
| Standard Function        | DST, Automatic Status Switch, Anti-passback, Scheduled-Bell, PhotoID               |
| Power Supply             | 12V DC,3A  |
| Operating Temperature    | 0 °C- 45 °C  |
| Operating Humidity       | 20%-80%  |
| SDK                      | Standalone SDK   |
| Software                 | ZKAccess3.5  |

# Optional Accessories



Exit Button



FR1200



Electric Lock



Alarm




Sensor




RFID Reader

# Configuration



# Dimensions (mm)



ZKTeco Europe.

Av. Camino de lo Cortaio, 10. Nave 1.  
28703 San Sebastián de los Reyes. Madrid. SPAIN  
Tel: +34 916 532 891 E-mail: sales@zkteco.eu  
www.zkteco.eu

© Copyright 2016. ZKTeco Inc. ZKTeco Logo is a registered trademark of ZKTeco or a related company. All other product and company names mentioned are used for identification purposes only and may be the trademarks of their respective owners. All specifications are subject to change without notice. All rights reserved.

